University of Kalyani

Tender Ref. No.: KU/NIET/DETS/LAN/2026-27/03

Tender ID: 2026_UOK_1048364_1

CORRIGENDUM-1

AS PER NIT:

Feature	Description
Description	24 RJ-45 autosensing 10/100 /1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full 4 x 1G/10G SFP ports 1 x USB-C console port 1 x USB Type-A host port
Memory and Processor	Dual Core ARM Cortex A9 @1016 Mhz4 GB DDR3, Memory maximum 16 GB eMMC
Performance	Pv6 Ready Certified Latency 1 Gbps: 1.5 Sec , 10 Gbps: 1.8 Sec
Switching capacity	128 Gbps
Throughput capacity	95.2 Mpps
MAC table capacity	MAC address table size 16000 entries
Operating Temperature	Operating temperature :32°F to 113°F (0°C to 45°C) Operating relative humidity: 15% to 95% @ 104°F (40°C), noncondensing Acoustic Power: 0 dB, Pressure: 0 dB
Fans	Fixed fans
Electric Frequency	50/60Hz
Power Supplies	Fixed power supply
AC voltage	100–127 VAC / 200–240 VAC
Current	Max. Power : 33W
Maximum Power Rating	Management flexibility with support easy-to-use Web GUI, CLI
Idle power	IEC/EN 60825-1:2014, Class 1 Class 1 Laser Products/Laser Klasse 1
Lasers	UL 60950-1; CAN/CSA 22.2 No. 60950-1; EN 60825; IEC 60950-1; EN 60950-1
Safety	FCC Class A; EN 55022/CISPR-22 Class A; VCCI Class A
Emissions	Generic: EN 55024, CISPR 24; EN : EN 55024, CISPR 24; ESD : IEC 61000-4-2; Radiated : IEC 61000-4-3; EFT/Burst : IEC 61000-4-4 Surge : IEC 61000-4-5; Conducted : IEC 61000-4-6; Power frequency magnetic field : IEC 61000-4-8; Voltage dips and interruptions: IEC 61000-4-11; Harmonics EN 61000-3-2, IEC 61000-3-2; Flicker EN 61000-3-3, IEC 61000-3-3
Immunity	Life Time warranty by OEM
Warranty	24 RJ-45 autosensing 10/100 /1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full 4 x 1G/10G SFP ports 1 x USB-C console port 1 x USB Type-A host port

TO BE READ AS :

Feature	Description
Description	24 RJ-45 autosensing 10/100 /1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full 4 x 1G/10G SFP ports 1 x USB-C console port 1 x USB Type-A host port
Memory and Processor	Dual Core ARM Cortex A9 @1016 Mhz4 GB DDR3, Memory maximum 16 GB eMMC
Performance	Pv6 Ready Certified Latency 1 Gbps: 1.5 Sec , 10 Gbps: 1.8 Sec
Switching capacity	128 Gbps
Throughput capacity	95.2 Mpps
MAC table capacity	MAC address table size 16000 entries
Operating Temperature	Operating temperature :32°F to 113°F (0°C to 45°C) Operating relative humidity : 15% to 95% @ 104°F (40°C), noncondensing Acoustic Power: 0 dB, Pressure: 0 dB
Fans	Fixed fans
Electric Frequency	50/60Hz
Power Supplies	Fixed power supply
AC voltage	100–127 VAC / 200–240 VAC
Maximum Power Consumption	Max. Power : 33W
Management Features	Management flexibility with support easy-to-use Web GUI, CLI
Lasers	IEC/EN 60825-1:2014, Class 1 Class 1 Laser Products/Laser Klasse 1
Safety	UL 60950-1; CAN/CSA 22.2 No. 60950-1; EN 60825; IEC 60950-1; EN 60950-1
Emissions	FCC Class A; EN 55022/CISPR-22 Class A; VCCI Class A
Certificate	Generic: EN 55024, CISPR 24; EN : EN 55024, CISPR 24; ESD : IEC 61000-4-2; Radiated : IEC 61000-4-3; EFT/Burst : IEC 61000-4-4 Surge : IEC 61000-4-5; Conducted : IEC 61000-4-6; Power frequency magnetic field : IEC 61000-4-8; Voltage dips and interruptions: IEC 61000-4-11; Harmonics EN 61000-3-2, IEC 61000-3-2; Flicker EN 61000-3-3, IEC 61000-3-3
Warranty	Life Time warranty by OEM

Bidders are advised to note the above before final submission of their bids.

Sd/−
Tender Inviting Authority
University of Kalyani